

# SPECIFICATION SHEET - ROLLING DOORS

## 24 GA - GALVANIZED STEEL SERVICE DOOR




[chiohd.com](http://chiohd.com)

1485 Sunrise Dr.  
Arthur, IL 61911  
Phone: (800) 677-2650

# Model 6241

## FLAT SLAT

### STANDARD FEATURES 12'0" x 14'4" Maximum Dimensions



- 24 gauge galvanized steel slat
- Minimum 11 gauge, double steel angle bottom bar
- Minimum 1/8" structural steel angle guides
- Minimum 1/8" headplates
- 24 gauge half-hexagonal galvanized steel hood
- Steel barrel with maximum deflection of 0.03" per foot of width.

- Helical wound torsion spring assemblies, grease packed and designed for 20 cycles per day.
- Precision, self-aligning sealed bearing
- Standard construction to withstand 20 p.s.f. per ASTM E330

### COLORS & POWDER COATING

- **Prefinished Curtains:** Gray, White, Tan, Brown, Galvanized, Powder Coat
- **Hood:** Color to match curtain
- **Guides:** Black [Standard], Powder Coat, Cold Spray Galv.
- **Headplates:** Black [Standard], Powder Coat, Cold Spray Galv.
- **Bottom Bar:** Galvanized, Powder Coat

### OPERATION

- Manual push-up with dual slides locks standard for doors up to 10'4" x 8'4"
- Chain Hoist standard for doors larger than 10'4" wide or 8'4" tall
- Motor operation optional, Front of Hood or Wall mount

### HARDWARE

- **Endlocks:** Cast, malleable and zinc plated for wear and durability.
- Lag bolts for wood jambs or self-tapping bolts for steel jambs standard. Masonry options available.
- Lock options available. Vary by door size and operation.

### WEATHER SEAL

- **Standard:** Bottom astragal
- **Optional:** Vinyl guide seal, rubber hood baffle, jamb brush seal, header brush seal

### FENESTRATION

- **Window Lites:** 5" x 1-1/8" openings, 7" centers. Clear acrylic glazing.
- **Cutouts only:** 5" x 1-1/8" openings, 7" centers. No glazing.

### FRAMING / INSTALLATION

All installation quality and workmanship is responsibility of contractor and is to be executed in accordance with C.H.I. installation instructions, local and state building codes and work site safety regulations.

- Face of wall and above lintel
- Face of wall and under lintel
- Between jamb and above lintel
- Between jamb and under lintel